


2 YEARS
warranty



DESCRIPTION

Thanks to its 3 independent temperature zones, Transtherm Castel combines three functions: storing, tempering and refreshing.

This high-capacity wine cabinet comes with 3 rolling shelves and 3 storing shelves. Using this configuration, the wine cabinet holds 190 bottles*.



1825/72

720/29

RANGE
Prestige

MODEL
Castel
glass door

FUNCTION
triple-zone


CAPACITY
190 bottles*

INTERIOR LAYOUT
storing pack

GENERAL FEATURES

| |
|--|
| Stand Alone fridge (can be built-in according to specifications) |
| 3-temperature product : to temper, chill and store wine |
| Glass door |
| Black frame or silver frame |
| Black stainless steel handle, removable |
| Reversible door |
| Lock system |
| Body colors : Black or Tobacco |
| 2 front feet adjustable |
| 3 sliding shelves in steel with wood front |
| 3 storing shelves in wood |
| 2 isolated compartments in wood |
| 190 Bordeaux bottles capacity |
| White display |
| White lighting : 2 Leds under the control panel |
| Real temperature display |

INTERNAL LAYOUT



x3

Sliding shelf ACUPHT
1,8 kg
W535xD525xH28mm
Steel with front wood
up to 12 bottles



x3

Storing shelf AXUHT
1,8 kg / W535xD525xH28mm
Solid Beechwood with ecological water varnish
up to 77 bottles / 100kg

OPTIONAL SHELVES



Presentation shelf ACPHT
1,8 kg / W535xD535xH110mm
Solid Beechwood with ecological water varnish
up to 22 bottles

TECHNICAL FEATURES

| | |
|---|--|
| Electronic regulation | plastic grey, with sensitive touch |
| Tempering compartment capacity | 11 bottles* |
| Setting range for tempering compartment | From 15°C / 59°F to 20°C / 68°F |
| Setting range for the main compartment | From 9°C / 48°F to 15°C / 59°F |
| Chilling compartment capacity | 14 bottles* |
| Setting range for chilling compartment | Induced by the one of the main compartment |
| Default temperature setpoint | 12°C / 54°F (main compartment) 18°C / 64°F (temper compartment) |
| Unit temperature setting | °C or °F |
| Lighting regulation | OFF/ON/At door opening |
| Alarms | Visual |
| Type of alarms | Temperature, sensor default |
| Ambient operating temperature | Between 12°C / 54°F and 30°C / 86°F |
| Climate class | SN-T |
| Winter mode | Yes, automatic |
| Energy consumption class | G |
| Annual energy consumption | 176 kWh/year |
| Sound Emission level | 37 dB(A) |
| Sound Emission class | C |

FUNCTIONALITY AND STRUCTURE

| | |
|--------------------------------------|--|
| Useful volume | 446 L |
| Cold production | Static |
| Compressor | R600a Gas |
| Heat release | Heater |
| Inner material | Aluminium |
| Exterior coating material | Hight pressure laminates panels HPL |
| Insulaions type | polyurethan foam (59mm) |
| Maximumm capacity | 209 |
| Interior layout for maximum capacity | 3 storing shelves |
| Packed product dimensions | H 1910 x W 733 x D 768 mm H 75 x W 29 x D 30 inch |
| Product dimensions | H 1825 x W 680 x D 720 mm H 72 x W 27 x D 29 inch |
| packed product weight | 106 kg |
| Net weight | 97 kg |
| Country of origin | France |